

## Notice

This manual provides general information, preparation for use, installation and operating instructions for the Black Lion Audio Revolution Clock Mini.

The information contained in this manual is subject to change without notice. Black Lion Audio makes no warranties of any kind with regard to this manual, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Black Lion Audio shall not be liable for errors contained herein or direct, indirect, special, incidental, or consequential damages in connection with the furnishing, performance, or use of this material.

©2024 Black Lion Audio. The Black Lion Audio 'Lion Face' logo, BLA, Revolution Clock Mini are trademarks or registered trademarks of Black Lion Audio. This manual and any associated intellectual property are subject to copyright protection. No part of this document may be reproduced in any form without explicit written consent from Black Lion Audio.


**RAD Distribution**  
180 Carpenter Ave.  
Middletown, NY 10940

Revised 12-30-25



# Revolution Clock Mini

Word clock with Macro MMC



Owner's Manual

## IMPORTANT SAFETY INSTRUCTIONS

1. Read these instructions.
2. Keep these instructions.
3. Heed all warnings.
4. Follow all instructions.
5. Do not use this apparatus near water.
6. Clean only with dry cloth.
7. Install in accordance with the manufacturer's instructions.
8. Do not install near any heat sources such as radiators, heat registers, stoves, or other apparatus that produce heat.
9. Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding-type plug has two blades and a third grounding prong. The wide blade or third prong is provided for your safety. If the provided plug does not fit into your outlet, consult an electrician for replacement of the obsolete outlet.
10. Protect the power cord from being walked on or pinched particularly at plugs, convenience receptacles, and the point where they exit from the apparatus. If the power cord becomes frayed, stop using immediately.
11. Use only attachments/accessories specified by the manufacturer.
12. Use only with a cart, stand, tripod, bracket or table specified by the manufacturer, or sold with the apparatus. When a cart is used, use caution when moving the cart/apparatus combination to avoid injury from tip-over.
13. Unplug this apparatus during lightning storms or when unused for long periods of time.
14. Refer all servicing to qualified service personnel. Servicing is required when the apparatus has been damaged in any way, such as power supply cord or plug is damaged, liquid has been spilled or objects have fallen into the apparatus, the apparatus has been exposed to rain or moisture, does not operate normally, or has been dropped.
15. This apparatus shall not be exposed to dripping or splashing, and no object filled with liquids, such as vases, shall be placed on the apparatus.
16. Note that this apparatus is not completely disconnected from the AC mains service when the power switch is in the OFF position.
17. The mains plug or power inlet on the product is used as the disconnect device, so the disconnected device shall remain readily operable when reconnected.
18. Any changes or modifications not expressly approved in this manual could void your authority to operate this apparatus.

## IMPORTANT!

Be sure to use a three prong AC cable that properly fits the power source. Please use the correct fuse designated on the rear panel before plugging in the power cord. Improper selection can result in damage to the unit that will not be covered under the warranty.

The lightning flash with an arrowhead symbol within an equilateral triangle is intended to alert the user to the presence of uninsulated "dangerous voltage" within the product's enclosure that may be of sufficient magnitude to constitute a risk of electric shock to persons.



The exclamation point within an equilateral triangle is intended to alert the user to the presence of important operating and maintenance (servicing) instructions in the literature accompanying the product.



The Black Lion Audio Revolution Clock Mini complies with all applicable RoHS/WEEE European Union directives.

**Do not attempt to service this unit yourself, as it will void your warranty. Please check your unit carefully upon receipt and return to place of purchase immediately if there are any problems with the product. After that, the standard Black Lion Audio 3 YEAR warranty will apply to defects in materials and workmanship.**

### U.S.A.

Should your Black Lion Audio product require service, please contact us on our customer service site: <https://www.blacklionaudio.com/contact>. You must obtain an RA # (Return Authorization number) from us before shipping a unit back to us. This RA # must be clearly written on the outside of the box.

**Please safely pack the units...It is best to use the original packing materials. Black Lion Audio cannot be responsible for any damages incurred in shipping to us due to poor packaging. PLEASE PACK CAREFULLY and FULLY INSURE THE SHIPMENT.**

### INTERNATIONAL

For service or warranty assistance, please contact the Black Lion Audio distributor in your country through the dealer from whom you purchased this product.

### LIMITED 3 YEAR WARRANTY

Black Lion Audio's Revolution Clock Mini is warranted by Black Lion Audio to be free from defects in materials and workmanship for the period of THREE (3) YEARS to the original purchaser. In the event of such defects, the product will be repaired without charge or, at our option, replaced with a new one if delivered to Black Lion Audio prepaid, together with a copy of the sales slip or other proof of purchase date. The warranty excludes problems due to normal wear, abuse, shipping damage or failure to use the product in accordance with the specifications.

All parts and labor are covered under this Limited Warranty. However, if it is determined by Black Lion Audio that the device was damaged or made defective through abuse, we reserve the right to charge the customer for the cost of the repair.

Black Lion Audio shall not be liable for damages based upon inconvenience, loss of use of the product, loss of time, interrupted operation or commercial loss or any other damages, whether incidental, consequential or otherwise. This warranty gives you specific legal rights, and you may have other rights, which will vary from state to state.

**This warranty is not transferable.**


## THANK YOU!

Thanks for choosing the Revolution Clock Mini. It will provide you with crystal-clear synchronization for years to come. Your studio (and your clients) will all be better off for it!

## MACRO-MMC

Revolution Clock Mini also uses our Macro-MMC clocking technology, which is based off of everything we learned from modifying audio interfaces for superior clocking and conversion.

Macro-MMC's circuit implementation will bring your converters' performance to new heights.



**1. Sample rate selectors:** Use SAMPLE RATE in conjunction with OUTPUT FREQUENCY to choose the desired sample rate. Choose from 44.1kHz-192 kHz.

Sample rate	1x	2x	4x
44.1	44.1	88.2	176.4
48	48	96	192

**2. Power indications:** Lights when unit is powered on.

**3. Power switch:** Toggles the unit on/off.

**4. DC in:** Provides power to the unit. Connect included DC adapter here.

**5. BNC outputs:** 5V, 75Ω outputs; self-terminated. Connect devices to be synced to Revolution Clock Mini here.

### Tips

When using BNC connections, we recommend a max cable length of 1,000 ft. Be sure to use high-quality 75Ω coaxial cable. It is unnecessary to engage the 75Ω termination button on the receiving device or to use an external terminator in the setup configuration. Additional methods of termination make the clock outputs work harder than necessary.

## SPECIFICATIONS

<b>Jitter</b>	0.5 pS RMS(BNC outputs)
<b>Outputs</b>	3x BNC
<b>Output impedance</b>	75Ω, 5V unterminated
<b>Clock frequencies</b>	44.1, 48, 88.2, 96, 176.4, 192
<b>Power</b>	9V DC (6 W power consumption)
<b>Power connector</b>	2.5 mm barrel connector with 5.5mm outer diameter (center pin positive)
<b>Dimensions</b>	Width: 15.24 cm (6") Height: 4.45 cm (1.75") Depth: 13.97 cm (5.5")
<b>Weight</b>	.91kg (2lbs)